(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date 11 March 2004 (11.03.2004)

PCT

(10) International Publication Number WO 2004/019699 A1

- (51) International Patent Classification⁷: A23L 1/00, A23J 3/10, 3/00, A23F 5/40, A23G 1/00, A23C 11/00
- (21) International Application Number:

PCT/EP2003/009384

- (22) International Filing Date: 22 August 2003 (22.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

EP

(30) Priority Data: 02078600.0

30 August 2002 (30.08.2002)

- (71) Applicant (for all designated States except US): CAMP-INA B.V. [NL/NL]; Hogeweg 9, NL-5301 LB Zaltbommel (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HOLTUS, Maria, Francisca [NL/NL]; St. Geertruikerhof 37, NL-5211 St Den Bosch (NL). BISPERINK, Christiaan, Gerrit, Jan [NL/NL]; Jacoba van Badenhof 28, NL-5371 EZ Ravenstein (NL). WINTJENS, Petrus, Albertina, Gerardus [NL/NL]; Lambertushof 13, NL-5481 CZ Schijndel (NL).

- (74) Agent: VAN SOMEREN, Petronella, Franscisca, Hendrika, Maria; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FOAMING INGREDIENT AND PRODUCTS CONTAINING THE INGREDIENT

(57) Abstract: The invention relates to a foaming ingredient for use in foamers and creamers. The foaming ingredient consists essentially of one or more proteins and optionally one or more plasticizers forming the wall of vacuoles that comprise entrapped gas. The amount of protein is preferably at least 88 % by weight and the amount of plasticizer lies between 0 and 10 %. Other minor additives may be present. The protein is preferably caseinate and the plasticizer glycerol or mannitol. The ingredient can be comprised in a foamer or creamer used in beverages, such as instant cappuccino and milkshakes.



1

FOAMING INGREDIENT AND PRODUCTS CONTAINING THE INGREDIENT

Field of the invention

The present invention relates to a foaming ingredient for use in foamers for instant food stuffs, in particular soluble beverages, like instant milkshakes and instant cappuccino. The invention further relates to foamers comprising such foaming ingredient and to the food stuffs that comprise these foamers.

Background of the invention

Instant powders that upon dissolution produce foaming beverages are particularly well known. Usually these powders are a dry mix of a soluble beverage powder and a soluble foamer. The soluble foamer contains vacuoles that contain gas which, upon dissolution of the powder, produce foam.

15 Therefore, upon the addition of (hot) water or milk, a beverage is formed, which has a foam on its upper surface.

A foamer ingredient for cappuccino-like beverages is for example the creamer ingredient known from EP-1074181. The creamer ingredient is produced from carbohydrate, protein and entrapped gas. The gas is present in an amount to release upon addition of liquid at least about 1 ml of gas at room temperature per gram of soluble creamer ingredient. The ingredient is part of the creamer that is used to whiten the coffee beverage.

25

30

Summary of the invention

The present inventors have now found that the above described creamer ingredient can be further improved with respect to foaming power and foam stability by using protein as the main ingredient and optionally a plasticizer or softener. It was found that by using mainly protein and

2

essentially no carbohydrate it became possible to produce more and smaller vacuoles than when carbohydrate was added as a further component. More vacuoles lead to more foam. Smaller vacuoles are stronger and therefore more stable. The strength and stability of the vacuoles are even further improved by the presence of a plasticizer. It was found that the higher amount of protein in the foaming ingredient of the invention in comparison to the prior art foaming ingredients causes the foam that is generated by it to be more stable over time.

In addition, it was found that the vacuoles, in particular the ones that are formed in the presence of a plasticizer, retain the entrapped gas for a longer period of time than vacuoles in a creamer ingredient that comprises carbohydrates. This can be explained as follows. The plasticizer makes the vacuole wall less brittle, resulting in practically no cracks in the vacuoles. It is possible to produce a functional foaming ingredient that is based solely on protein but such ingredient should be handled with care to avoid damage to the vacuole wall. It is therefore preferred to use a plasticizer or softener.

Accordingly, the invention relates to a foaming ingredient which essentially consists of one or more proteins and optionally one or more plasticizers forming the wall of vacuoles that comprise entrapped gas.

Detailed description of the invention

10

15

20

25

30

The term "essentially consisting of" is used herein to indicate that the amount of protein is at least 85% by weight, preferably at least 88% by weight, more preferably at least 90% by weight, even more preferably at least 92% by weight, and most preferably at least 94% by weight. The plasticizers are preferably selected from the group consisting of polyols or sugar alcohols, such as glycerol,

3

mannitol, sorbitol, lactitol, erythritol, trehalose and/or lipids, such as fatty acids, monoglycerides, phospholipids, and are used in an amount of 0-10% by weight, preferably 3-7% by weight, more preferably 4-6% by weight, most preferably 5% by weight. Preferably glycerol and/or mannitol are used.

The ingredient may comprise other additives in addition to the one or more proteins and the plasticizer. However, the foaming ingredient comprises no added carbohydrates. It may however be the case that the protein, such as caseinate, contains some residual carbohydrate. This is however present in very minor amounts in the protein preparation after manufacture thereof and not added as a constituent of the foaming ingredient.

10

20

25

The other additives are preferably present in a minor amount. Examples of additives are emulsifiers, which are added to modify the size of the vacuoles. Preferably monoand diglycerides are used.

It should be noted that the foaming ingredient can be used in a foamer that does comprise carbohydrates, for example for sweetening. However, according to the invention the material that forms the gas containing vacuoles does not comprise added carbohydrates.

The foaming ingredient can be made from a variety of proteins, such as milk proteins, e.g. caseinates, acid or rennet casein, native micellar casein (obtainable by microfiltration/ultrafiltration), whey protein isolate; egg protein; pea protein; wheat protein; soy protein or mixtures thereof. The proteins may also be used in the hydrolysed form, as peptide mixtures.

originates from milk. When the foaming ingredient is used in dairy-like products such as cappuccino foamer and creamer or milkshakes, the foamer can be an all-dairy product. In

4

addition, caseinate provides good foam stability, has a bland taste and has a neutral colour.

The foaming ingredient of the invention is obtainable by spray drying a protein solution that optionally comprises 5 a plasticizer, to obtain a powder, subjecting the powder to a gas under pressure at elevated temperatures to weaken the walls of the vacuoles existing in the powder particles to allow the vacuoles to take up the gas under pressure, cooling the powder to cure the vacuole walls and releasing the 10 pressure.

A suitable technique involves providing the vacuole wall material in the form of expanded particles and then entrapping gas in the particles. The expanded particles may be produced by injecting a gas into an aqueous solution of the vacuole wall material and then spray drying the concentrate to powder. The gas may be injected into the aqueous solution at a pressure of about 500 kPa to about 5 MPa. However, the pressure at which the gas is injected into the aqueous solution of vacuole wall material is not 20 critical. The gas may also be left out.

15

25

An intermediate drying step, prior to the pressure treatment, may be incorporated in order to adjust the moisture content of the particles (formed by the vacuoles and their wall) to the right level.

The particles are then subjected to a gas atmosphere, preferably of an inert gas at high pressure and at a temperature above the glass transition temperature of the particles. The pressure may be from about 100 kPa to about 20 MPa. The temperature needed will depend upon the composition 30 of the vacuole wall material since this will influence the glass transition temperature. However, the temperature may be readily set for any material type by the skilled person. The particles may be subjected to the pressure and temperature

5

for as long as desired since increasing the time will generally increase the gas entrapment. Usually times of about 10 seconds to about 30 minutes are sufficient.

The particles are then subjected to quenching or curing to ensure entrapment of the gas. The particles can for example be sufficiently quenched by lowering the temperature. Once the particles are well below their glassy state, e.g. at 60°C below their glass transition temperature T_{G} , the pressure is released to ambient conditions.

The gas that is entrapped in the vacuoles may be any suitable food grade gas, such as nitrogen, carbon dioxide, N_2O , or air, and mixtures of these gases. Gases which are substantially inert are preferred.

15

20

25

As indicated above the foamer produced with the foaming ingredient of the invention may contain other components such as artificial sweeteners, emulsifiers, stabilisers, flowing agents, colours, flavours, aromas, and the like. Suitable artificial sweeteners include saccharin, cyclamates, acesulfame, L-aspartyl based sweeteners such as aspartame, and mixtures of these. Suitable emulsifiers include monoglycerides, diglycerides, lecithin, diacetyl tartaric acid esters of mono-diglycerides (DATEM esters), and mixtures thereof. Suitable stabilisers include dipotassium phosphate and sodium citrate. A suitable flowing agent is sodium silica aluminate.

The foaming ingredient of the invention may be used in a standard foamer or creamer in an amount of 10-80 weight%, preferably 20-60 weight%, most preferably 30-50 weight%.

The foamer or creamer, which is in a soluble form, may then be mixed with other components of the desired beverage or food stuff powder. Examples of such beverages are instant cappuccino, instant chocolate drinks, instant tea and

6

instant milkshake. Other non-beverage food stuffs are soups, sauces and desserts.

In this specification a foamer is a product that provides a foam upon dissolution, whereas a creamer has whitening power and may also provide a foam.

The present invention will be further illustrated in the examples that follow and that are not intended to limit the invention.

10 **EXAMPLES**

EXAMPLE 1

Preparation of foaming ingredient

1. Drying process

A mixture of 95 parts (w/w) sodium caseinate (EM-7, 15 DMV International) and 5 parts (w/w) glycerol was prepared. The mixture was dissolved in water to a solids content of about 15% by weight. After complete dissolution the mixture was fed to a spray dryer (type: nozzle dryer). Nitrogen gas was injected into the feedpipe of the nozzle and the mixture 20 was spray dried in the spray dryer and dried further in a fluidized bed to a moisture content of 3%.

2. <u>Gasloading process</u>

Subsequently, the powder was subjected to an
25 atmosphere of nitrogen gas at a pressure of about 3 MPa and a
temperature of 95°C for about 20 minutes. The powder was then
cooled to below 30°C after which the pressure was slowly
released.

30 3. <u>Hot coffee application</u>

The foaming ingredient powder was mixed with a soluble cappuccino foamer base (DP 387, DMV International), powdered sugar and a soluble coffee powder in a weight ratio

7

of 2.0: 4.0: 2.0: 2.0 to provide a soluble coffee beverage powder. An amount of 10 g of the resulting powder was placed in a beaker of about 0.05 m diameter and 100 ml of hot water (about 85°C) was added. The beverage was stirred twice. The beverage had an attractive light, fluffy foam with a height of about 0.035 m. The foam volume was about 70 ml.

4. Cold chocolate drink application

The foaming ingredient powder of the invention was

10 mixed with instantized (e.g. lecithinized) cocoa powder, skim
milk powder and sugar in a ratio of 1.0: 1.0: 4.0: 4.0 to
provide a cold soluble chocolate beverage powder. An amount
of 20 g of the resulting powder was placed in a beaker of
about 0.05 m diameter and 120 ml of cold water was added. The

15 beverage was stirred for 15 seconds. The beverage had a
light, fluffy and stable foam of height about 0.02 m and was
stable for at least 1 hour. The foam volume was about 40 ml.

EXAMPLE 2 (comparative)

20 <u>Coffee application</u>

25

30

The hot soluble coffee beverage powder of example 1 (A) was compared to a hot soluble beverage powder (B) in which the foaming ingredient was prepared according to example 2 of European patent application EP-1 074 181. Sample B contains the same amount of foaming ingredient, DP387, powdered sugar and soluble coffee powder (in a weight ratio of 2.0 : 4.0 : 2.0 : 2.0) as sample (A).

10 grams of each powder was placed in a beaker of about 0.05 m diameter and 100 ml of hot water (85°C) was added. The resulting beverage was stirred twice. The foam heights and volumes were as follows:

8

Sample	Foam height	Foam volume	
	(m)	(ml)	
A	0.035	70	
В	0.02	40	

5 EXAMPLE 3 (comparative)

Cold chocolate drink application

The cold soluble beverage powder of example 1 (A) was compared to a cold soluble beverage powder (B) in which the foaming ingredient was prepared according to example 2 of

10 European patent application EP-1 074 181. Both samples (A and B) contain the same amounts of foaming ingredient, powdered sugar, cocoa powder and skim milk powder (in a weight ratio of 1.0 : 1.0 : 4.0 : 4.0)

20 Grams of each powder was placed in a beaker of
15 about 0.05 m diameter and 120 ml of cold water was added. The
resulting beverage was stirred for 15 seconds. The foam
heights and volumes were as follows:

Samp	le F	'oam		Foam	volume
	h	eight	(m)	(ml)	
A	0	.02		40	
В	0	.008		16	

CLAIMS

- 1. Foaming ingredient which essentially consists of one or more proteins and optionally one or more plasticizers forming the wall of vacuoles that comprise entrapped gas.
- 2. Foaming ingredient as claimed in claim 1, wherein the amount of protein is at least 85% by weight.
 - 3. Foaming ingredient as claimed in any one of claims 1 and 2, wherein the amount of protein is at least 88% by weight.
- 4. Foaming ingredient as claimed in any one of claims 10 1-3, wherein the amount of protein is at least 90% by weight.
 - 5. Foaming ingredient as claimed in any one of claims 1-4, wherein the amount of protein is at least 92% by weight.
 - 6. Foaming ingredient as claimed in any one of claims 1-5, wherein the amount of protein is at least 94% by weight.
- 7. Foaming ingredient as claimed in any one of claims 1-6, which comprises no added carbohydrates.
 - 8. Foaming ingredient as claimed in any one of the claims 1-7, wherein the one or more plasticizers are polyols or sugar alcohols and/or lipids.
- 9. Foaming ingredient as claimed in claim 8, wherein the polyols or sugar alcohols are selected from the group consisting of glycerol, mannitol, sorbitol, lactitol, erythritol, threhalose.
- 10. Foaming ingredient as claimed in claim 8, wherein 25 the lipids are selected from the group consisting of fatty acids, monoglycerides, phospholipids.
 - 11. Foaming ingredient as claimed in any one of the claims 1-10, wherein the one or more plasticizers are present in an amount of 0-10% by weight, preferably 3-7% by weight,
- 30 more preferably 4-6% by weight, most preferably 5% by weight.

WO 2004/019699

15

- 12. Foaming ingredient as claimed in any one of the claims 1-11, further comprising a minor amount of additives.
- 13. Foaming ingredient as claimed in claim 12, wherein the additive is one or more emulsifier.
- 5 14. Foaming ingredient as claimed in claim 13, wherein the emulsifier is a monoglyceride or a diglyceride or a combination thereof.
- 15. Foaming ingredient as claimed in any one of the claims 1-14, wherein the protein is selected from the group consisting of milk proteins, e.g. caseinates, acid or rennet casein, native micellar casein, whey protein isolate; egg protein; pea protein; wheat protein; soy protein; mixtures thereof or hydrolysed forms thereof.
 - 16. Foaming ingredient as claimed in claim 15, wherein the protein is caseinate.
- 17. Foaming ingredient as claimed in any one of the claims 1-16 obtainable by spray drying a protein solution that optionally comprises a plasticizer, to obtain a powder, subjecting the powder to a gas under pressure at elevated

 20 temperatures to weaken the walls of the vacuoles existing in the powder particles to allow the vacuoles to take up the gas under pressure, cooling the powder to cure the vacuole walls and releasing the pressure.
- 18. Foaming ingredient as claimed in any one of the
 25 claims 1-17 for use in foamers or creamers for cappuccinotype beverages, milkshakes, instant chocolate drinks, instant
 tea, soups, sauces, desserts.
 - 19. Foamer, comprising a foaming ingredient as claimed in claims 1-18.
- 30 20. Creamer, comprising a whitening agent and a foaming ingredient as claimed in claims 1-18.

11

- 21. Instant cappuccino comprising a soluble coffee powder and a soluble creamer, which creamer comprises a foaming ingredient as claimed in claims 1-18.
- 22. Instant milkshake comprising a soluble milkshake 5 powder and a soluble foamer, which foamer comprises a foaming ingredient as claimed in claims 1-18.
 - 23. Method for preparing a foamer ingredient as claimed in claims 1-18, comprising the steps of:
- a) spray drying a protein solution that optionally 10 comprises a plasticizer, to obtain a powder;
 - b) subjecting the powder to a gas under pressure at elevated temperatures to weaken the walls of the vacuoles existing in the powder particles to allow the vacuoles to take up the gas under pressure;
 - c) cooling the powder to cure the vacuole walls; and
 - d) releasing the pressure.

15

INTERNATIONAL SEARCH REPORT

PCT/EP 03/09384

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A23L1/00 A23C A23J3/10 A23J3/00 A23F5/40 A23G1/00 A23C11/00 According to International Patent Classification (IPC) or to both national classification and IPC **B. FIELDS SEARCHED** Minimum documentation searched (classification system followed by classification symbols) IPC 7 A23L A23J A23F A23G A23C Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) WPI Data, PAJ, EPO-Internal, FSTA C. DOCUMENTS CONSIDERED TO BE RELEVANT Category ° Citation of document, with indication, where appropriate, of the relevant passages Retevant to claim No. X EP 0 813 815 A (KRAFT FOODS INC) 1,8, 29 December 1997 (1997-12-29) 18-22 claims 1-16 X EP 1 228 694 A (NESTLE SA) 1,8,23 7 August 2002 (2002-08-07) paragraph '0048!; claims 1-4 X WO 02 060283 A (UNILEVER PLC ; LEVER 1,12,15 HINDUSTAN LTD (IN); UNILEVER NV (NL)) 8 August 2002 (2002-08-08) claims 1-8,21,22 EP 1 074 181 A (NESTLE SA) Α 1,18-237 February 2001 (2001-02-07) cited in the application page 3; claims 1-10; example 2 Further documents are listed in the continuation of box C. lχ Patent family members are listed in annex. Special categories of cited documents: *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the "A" document defining the general state of the art which is not considered to be of particular relevance invention "E" earlier document but published on or after the international *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled O document referring to an oral disclosure, use, exhibition or other means document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 10 November 2003 25/11/2003 Name and mailing address of the ISA Authorized officer European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016 Desmedt, G

Information on patent family members

PCT/EP 03/09384

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0813815	Α	29-12-1997	AT CA	238679 T 2205773 A1	15-05-2003 21-12-1997
			CN	1170542 A	21-01-1998
			DE	69721385 D1	05-06-2003
			EP	0813815 A1	29-12-1997
			HU	9701077 A2	30-03-1998
			JP	10066531 A	10-03-1998
			PL	320653 A1	22-12-1997
EP 1228694	 А	07-08-2002	EP	1228694 A1	07-08-2002
			CA	2436897 A1	26-09-2002
			WO	02074096 A2	26-09-2002
WO 02060283	Α	08-08-2002	WO	02060283 A2	08-08-2002
			EP	1355544 A2	29-10-2003
			US	2002155208 A1	24-10-2002
EP 1074181	Α	07-02-2001	EP	1074181 A1	07-02-2001
			AU	6697800 A	19-02-2001
			BR	0012977 A	23-04-2002
			CA	2379174 A1	08-02-2001
			CN	1377233 T	30-10-2002
			MO	0108504 A1	08-02-2001
			EP	1206193 A1	22-05-2002
			HU	0202302 A2	28-10-2002
			JP	2003505098 T	12-02-2003
			US	2002127322 A1	12-09-2002

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.